



TOLERANCES	LINEAR-DIMENSION				
	>6-30	>30-60	>60-120	>120-200	>200-300
ALL MACHININGS mm	±0.2	±0.3	±0.7	±1	±3

Specification:

1. Nominal pressure: 1.6MPa;
2. Working medium: Water, Gas, Oil (Non-corrosive) ;
3. Working temperature: -10°C to 120 °C;
4. Thread standard: according to ISO228-1;

CODE NO.	E	DN	L	L1	L2	E1	A	weight
333700-015	1/2	3.8	75	286	30	M8	34	290
333700-020	3/4	5	92	340	30	M8	34	480
333700-025	1	9	102	420	36.5	M10	44.5	720
333700-032	1-1/4	11.5	147	422	41	M12	60	1522
333700-040	1-1/2	14.5	158	452	52	M12	60	1625
333700-050	2	19	156	542	50	M12	60	1705

10	CASE	BRASS
9	TIE ROD	BRASS
8	PIN	BRASS
7	ROTOR	BRASS
6	PRESS NUTS	BRASS
5	O-RING	NBR
4	TIE-IN	BRASS
3	GASKET	NBR
2	CORE	BRASS
1	BODY	BRASS
ITEM	NAME	MATERIAL

TOLERANCES	LINEAR-DIMENSION					REMARK: 1.THE UNIT WEIGHT CAN BE ACCEPTED WITH IN ±5%. 2.THE TOLERANCE CAN BE ACCEPTED AS THE SHEET.	BRASS FLOAT VALVE (HP) 15MM-50MM DATED: MAY 24, 2016
	>6-30	>30-60	>60-120	>120-200	>200-300		
ALL MACHININGS mm	±0.2	±0.3	±0.7	±1	±3		